

12", 18", 24" Wide Conveyor



GRAIN MASTER

Features and Options

- *Designed for Durability and Performance*
- *Capacity up to 10,000 Bushels per Hour*
- *Rubber Crescent Top Belt*
- *Folding Canvas Hopper*
- *Hot Dipped Galvanized Finish*
- *Electric or Gas Drive Options Available on some Models*
- *Optional Hydraulic Drive on some Models*
- *Other Sizes Available , Call for Information*



www.tmwattachments.com



12", 18", 24" Wide Conveyors Specifications

Model	2412	3412	4412	3418	4418	5418	6418	7418
Overall Length	24'	34'	44'	34'	44'	54'	64'	74'
Conveyor Width	16"	16"	16"	22"	22"	22"	22"	22"
Height Under Spout at 30 Degree	14'	16'	22'	16'	22'	26'	29'	36'
Belt Widths	12"	12"	12"	18"	18"	18"	18"	18"
Bushels per Hour	4,500	4,500	4,500	8,000	8,000	8,000	8,000	8,000
Galvanized Finish	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Electric Motor HP	5 HP	5 HP	7.5 HP	7.5 HP	7.5 HP	15 HP	15 HP	20 HP
Single Phase Motor	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
3 Phase Motor	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hydraulic Belt Drive	Yes	Yes	Yes	Yes	Yes	No	No	No
GX Series Honda Gas Motor	No	No	No	No	No	Yes	Yes	Yes
Top Drive	Yes	Yes	Yes	Yes	Yes	No	No	No
Bottom S Pinch Drive	No	No	No	No	No	Yes	Yes	Yes

GX Series Honda Motors have a 3 Year Warranty
Honda Test Engineers have Approved each Application

Model	5424	6424	7424
Overall Length	54'	64'	74'
Conveyor Width	28"	28"	28"
Height Under Spout at 30 Degree	26'	29'	36'
Belt Widths	24"	24"	24"
Bushels per Hour	10,000	10,000	10,000
Galvanized Finish	Std.	Std.	Std.
Electric Motor HP	20 HP	30 HP	30 HP
Single Phase Motor	No	No	No
3 Phase Motor	Yes	Yes	Yes
GX Series Honda Gas Motor	No	No	No
Bottom S Pinch Drive	Yes	Yes	Yes

Your TMW Dealer



522 Meeker Avenue • East Eden Valley, MN 55329
www.tmwattachments.com



© 2013 TMW